

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ENOVALITE

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: ELED500123

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD2835		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	200	Energy efficiency class	E
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	24 000 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode power (P_{on}), expressed in W	200,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	1 115	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	115	
	Depth	105	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,342 0,358
Parameters for LED and OLED light sources:			
R9 colour rendering index value	80	Survival factor	-
the lumen maintenance factor	-		
Parameters for LED and OLED mains light sources:			
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,9

(a)-: not applicable;

(b)-: not applicable;

Spectrum Test Report


Product Information

Product Type: H018E-200W
Product Number: 1

Product Spec: 5000K

CIE Colorimetric Parameters

Chromaticity coordinates: $x=0.3423$ $y=0.3584$ $u(u')=0.2070$ $v=0.3250$ $v'=0.4875$
 CCT: $T_c=5126K$ ($duv=0.00447$) Color Ratio: $R=0.150$ $G=0.809$ $B=0.042$
 Peak Wavelength: 0nm Half Bandwidth: 20.0nm
 Dominant Wavelength: 567.8nm Color Purity: 0.103
 CRI: R_i : $R_a=81.8$
 $R_1=81$ $R_2=82$ $R_3=82$ $R_4=88$ $R_5=81$ $R_6=75$ $R_7=90$ $R_8=75$
 $R_9=12$ $R_{10}=56$ $R_{11}=87$ $R_{12}=49$ $R_{13}=80$ $R_{14}=90$ $R_{15}=78$



Photometric Parameters

Luminous Flux: 19934.4 lm Efficiency: 99.35 lm/W

Electric Parameters

Voltage: 230.70V Current: 0.8750A Power: 200.650W
 Power Factor: 0.994 Frequency: 50.00Hz

Test Information


Scan Range: 380nm~800nm:1nm
 Stabilization Time: 0 Min
 Max of Signal: 12574 (37475)

Photometric Method:
 Photometric Condition: Sphere diameter: 1.00m, 4π
 CCD Integration Time: 69.88 ms

Condition:
 Test Lab:
 Operator:

Test Device: Inventfine CMS-2S
 Test Time:
 Inspector:

Model placed on the Union market from 09/12/2022



EPREL registration number: 1785288

<https://eprel.ec.europa.eu/qr/1785288>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213

26441 Jever

Germany