

Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUXULA

Supplier's address: ENOVATEK GmbH, Sillensteder Straße 213, 26441 Jever, DE

Model identifier: LX500136

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	SMD 2835		
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	150	Energy efficiency class	F
Useful luminous flux (ϕ_{use}), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	15 000 in Nar-row cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000 or 5 000 or 6 500
On-mode power (P_{on}), expressed in W	150,0	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer dimensions without separate control gear, lighting control	Height	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width		
	Depth		

parts and non-lighting control parts, if any (millimetre)				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-	
		Chromaticity coordinates (x and y)	0,440 0,403	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	80	Survival factor	-	
the lumen maintenance factor	0,70			
Parameters for LED and OLED mains light sources:				
displacement factor (cos ϕ_1)	0,90	Colour consistency in McAdam ellipses	6	
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-	
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	-	

(a) '-': not applicable;

(b) '-': not applicable;


Spectrum Test Report

Sample	:		Date	:	2021-01-10 13:15:59
Specification	:		Sam. Status	:	
Sample No.	:	LX500136	Standard	:	
Manufacturer	:		Instrument	:	HaasSuite(EVERFINE)
Assessor	:	damin		:	
Remark	:	--	Test by	:	DAMIN

Test Condition

Temperature	:	25.3Deg	RH	:	65.0%
WL Range	:	380nm-780nm	IP	:	50066 (76%)
Test Mode	:	Fast Test	T	:	185 ms

Spectrum : High



Colorimetric Parameters

Chromaticity Coordinate: $x = 0.3841$ $y = 0.3837$ / $u' = 0.2248$ $v' = 0.5051$ ($duv=2.14e-03$)

CCT= 3953K Prcp WL: $L_d=578.2nm$ Purity=30.4%

Peak WL: $L_p=595nm$ FWHM: $=154.3nm$ Ratio: R=18.4% G=78.4% B=3.2%

Render Index: $R_a = 83.0$

EEL: 0.13222 A+

R1=81 R2=87 R3=92 R4=84 R5=82 R6=83 R7=87

R8=68 R9=13 R10=70 R11=83 R12=65 R13=82 R14=96 R15=75

Photometric & Radiometric Parameters

Flux = 15228 lm Eff.: 103.02 lm/W Fe = 46.702 W

Electrical parameters


V = 230.09 V I = 0.6474 A P = 147.8 W PF = 1.056 F=50.00 Hz

Kdisp(IEC) = 0.9998

EVERFINE CORPORATION

<http://www.everfine.cn>

Model placed on the Union market from 31/05/2024



EPREL registration number: 1997380

<https://eprel.ec.europa.eu/qr/1997380>

Supplier: ENOVATEK GmbH (Importer)

Website: www.enovatek.de

Customer care service:

Name: ENOVATEK GmbH

Website: www.enovatek.de

Email: info@enovatek.de

Phone: +49 4461 / 7464233

Address:

Sillensteder Straße 213
26441 Jever
Germany